



Model	Power		Max head m	Max.flow m <sup>3</sup> /h	Size Inch	N/W kg	Q (m <sup>3</sup> /h) Q (L/min)	0	2	4	6	8	10	12	14
	kW	HP						0	33.3	66.7	100	133.3	166.7	200	233.3
GPS400F	0.4	0.55	6	7	1" / 1 1/4"	4.2		6	4.2	2.1	0.6				
GPS550F	0.55	0.75	7	8	1" / 1 1/4"	5.1		7	5.4	4	2.3	0.2			
GPS750F	0.75	1	8	11	1" / 1 1/4"	5.4		8	6.5	4.9	3.3	2.2	0.6		
GPS900F	0.9	1.2	9	13	1" / 1 1/4"	5.3		9	7.6	5.7	4.3	2.8	1.1	0.6	
GPS551F	0.55	0.75	6.5	10	1" / 1 1/4" / 1 1/2"	5.1		6.5	6	5.5	4.5	2.5	0		
GPS751F	0.75	1	7.5	13	1" / 1 1/4" / 1 1/2"	5.5		7.5	7.1	6.5	5.8	4.5	3.5	1.5	
GPS901F	0.9	1.2	8.5	14	1" / 1 1/4" / 1 1/2"	5.7		8.5	8	7.5	7	6	4	3	
GPS1101F	1.1	1.5	11	15	1" / 1 1/4" / 1 1/2"	6.6		11	10	9	8.5	7	6	4.5	1.5



GPSXX2F



GPSXX3F



GPSXX4F



Model	Power		Max head m	Max.flow m <sup>3</sup> /h	Size Inch	N/W kg	Q (m <sup>3</sup> /h) Q (L/min)	0	2	4	6	8	10	12
	kW	HP						0	33.3	66.7	100	133.3	166.7	200
GPS402F	0.4	0.55	6	7	1" / 1 1/4"	4.9		6	5	4	2			
GPS552F	0.55	0.75	7	8	1" / 1 1/4"	5.1		7	6	5.5	3			
GPS752F	0.75	1	8	11	1" / 1 1/4"	5.2		8	7	6.5	5.5	4	2	
GPS902F	0.9	1.2	9	13	1" / 1 1/4"	5.3		9	8	7.5	6	5	3	1.5
GPS403F	0.4	0.55	5	8	1" 1/4" / 1 1/2"	4.3		5	4	3.5	2.7			
GPS553F	0.55	0.75	6.5	10	1" 1/4" / 1 1/2"	5		6.5	6	5	4	2.8		
GPS753F	0.75	1	7.5	13	1" 1/4" / 1 1/2"	5.4		7.5	7	6.5	5.8	4.5	3.5	1.5
GPS903F	0.9	1.2	8.5	14	1" 1/4" / 1 1/2"	5.4		8.5	8	7.5	6.8	5.5	4.5	2.8
GPS1103F	1.1	1.5	11	15	1" 1/4" / 1 1/2"	5.6		11	10	9.5	8.8	7	6	4.5

Model	Power		Max head m	Max.flow m <sup>3</sup> /h	Size Inch	N/W kg	Q (m <sup>3</sup> /h) Q (L/min)	0	1	2	3	4	5
	kW	HP						0	17	33	50	67	83
GPS904F	0.9	1.2	30	5	1" / 1 1/4" / 1 1/2"	6.5		30	28	26	25	15	
GPS1104F	1.1	1.5	35	5.5	1" / 1 1/4" / 1 1/2"	6.9		35	34	32	30	23	10